


PANEL NAME:				IP ADDRESS:					
MOUNTING LOCATION:				SUBNET MASK:					
TRANSFORMER FEED:				DEFAULT GATEWAY:					
PANEL TYPE:		NXL-D16s		PANEL DIMENSIONS:		24.00"H x 20.00"W x 6.00"D			
LEFT SIDE				RIGHT SIDE					
LOAD DESCRIPTION	SOURCE	ADDRESS	DEVICE	DEVICE	ADDRESS	SOURCE	LOAD DESCRIPTION		
CRC2180 RELAY CONTROLLER				CRC7000	0-1				
				CRC7000	0-2				
CRC2180 RELAY CONTROLLER				CRC7000	0-3				
				CRC7000	0-4				
	CHANNEL 1	4	-1	CRC4214 0-10 DIMMER	CRC7000	1-1			
	CHANNEL 2		-2						
	CHANNEL 3		-3			CRC7000	1-2		
	CHANNEL 4		-4						
	CHANNEL 1	5	-1	CRC4214 0-10 DIMMER	CRC7000	1-3			
	CHANNEL 2		-2						
	CHANNEL 3		-3			CRC7000	1-4		
	CHANNEL 4		-4						
	CHANNEL 1	6	-1	CRC4214 0-10 DIMMER	CRC7000	2-1			
	CHANNEL 2		-2						
	CHANNEL 3		-3			CRC7000	2-2		
	CHANNEL 4		-4						
	CHANNEL 1	7	-1	CRC4214 0-10 DIMMER	CRC7000	2-3			
	CHANNEL 2		-2						
	CHANNEL 3		-3			CRC7000	2-4		
	CHANNEL 4		-4						
CRC1301 (SPC) SPACE FOR CPU				CRC7000	3-1				
				CRC7000	3-2				
				CRC7000	3-3				
				CRC7000	3-4				
				SPACE					

INSTALLING CONTRACTOR TO USE: 16 AWG, BELDEN 6200 UE OR EQUAL; REFERENCE 2-WIRE DATA BUS WIRING DETAIL