


PANEL NAME:		IP ADDRESS:	N/A	
MOUNTING LOCATION:		SUBNET MASK:	N/A	
TRANSFORMER FEED:		DEFAULT GATEWAY:	N/A	
PANEL TYPE:	NXL-D24a	PANEL DIMENSIONS:	30.00"H x 24.00"W x 6.00"D	

LEFT SIDE				RIGHT SIDE			
LOAD DESCRIPTION	SOURCE	ADDRESS	DEVICE	DEVICE	ADDRESS	SOURCE	LOAD DESCRIPTION
		-1	CRC7000	CRC7000	-2		
		-3	CRC7000	CRC7000	-4		
		-1	CRC7000	CRC7000	-2		
		-3	CRC7000	CRC7000	-4		
		-1	CRC7000	CRC7000	-2		
		-3	CRC7000	CRC7000	-4		
		-1	CRC7000	CRC7000	-2		
		-3	CRC7000	CRC7000	-4		
		-1	CRC7000	CRC7000	-2		
		-3	CRC7000	CRC7000	-4		
		-1	CRC7000	CRC7000	-2		
		-3	CRC7000	CRC7000	-4		
		-1	CRC7000	CRC7000	-2		
		-3	CRC7000	CRC7000	-4		
	CHANNEL 1	-1	CRC4214 0-10V DIMMER	CRC4214 0-10V DIMMER	-4	CHANNEL 4	
	CHANNEL 2	-2			-3	CHANNEL 3	
	CHANNEL 3	-3			-2	CHANNEL 2	
	CHANNEL 4	-4			-1	CHANNEL 1	
	CHANNEL 1	-1	CRC4214 0-10V DIMMER	CRC4214 0-10V DIMMER	-4	CHANNEL 4	
	CHANNEL 2	-2			-3	CHANNEL 3	
	CHANNEL 3	-3			-2	CHANNEL 2	
	CHANNEL 4	-4			-1	CHANNEL 1	
	CHANNEL 1	-1	CRC4214 0-10V DIMMER	CRC4214 0-10V DIMMER	-4	CHANNEL 4	
	CHANNEL 2	-2			-3	CHANNEL 3	
	CHANNEL 3	-3			-2	CHANNEL 2	
	CHANNEL 4	-4			-1	CHANNEL 1	
SPACE				SPACE			
SPACE				SPACE			

INSTALLING CONTRACTOR TO USE: 16 AWG, BELDEN 6200 UE OR EQUAL; REFERENCE 2-WIRE DATA BUS WIRING DETAIL