


PANEL NAME:				IP ADDRESS:					
MOUNTING LOCATION:				SUBNET MASK:					
TRANSFORMER FEED:				DEFAULT GATEWAY:					
PANEL TYPE:		NXL-D24i		PANEL DIMENSIONS:		30.00"H x 24.00"W x 6.00"D			
LEFT SIDE				RIGHT SIDE					
LOAD DESCRIPTION	SOURCE	ADDRESS	DEVICE	DEVICE	ADDRESS	SOURCE	LOAD DESCRIPTION		
		0-1	CRC7000	CRC7000	0-2				
		0-3	CRC7000	CRC7000	0-4				
		1-1	CRC7000	CRC7000	1-2				
		1-3	CRC7000	CRC7000	1-4				
		2-1	CRC7000	CRC7000	2-2				
		2-3	CRC7000	CRC7000	2-4				
		3-1	CRC7000	CRC7000	3-2				
		3-3	CRC7000	CRC7000	3-4				
		4-1	CRC7000	CRC7000	4-2				
		4-3	CRC7000	CRC7000	4-4				
		5-1	CRC7000	CRC7000	5-2				
		5-3	CRC7000	CRC7000	5-4				
	CHANNEL 1	6	-1	CRC4214 0-10V DIMMER	CRC4214 0-10V DIMMER	7	-4	CHANNEL 4	
	CHANNEL 2						-3	CHANNEL 3	
	CHANNEL 3						-2	CHANNEL 2	
	CHANNEL 4						-1	CHANNEL 1	
	CHANNEL 1	8	-1	CRC4214 0-10V DIMMER	CRC4214 0-10V DIMMER	9	-4	CHANNEL 4	
	CHANNEL 2						-3	CHANNEL 3	
	CHANNEL 3						-2	CHANNEL 2	
	CHANNEL 4						-1	CHANNEL 1	
	CHANNEL 1	10	-1	CRC4214 0-10V DIMMER	CRC4214 0-10V DIMMER	11	-4	CHANNEL 4	
	CHANNEL 2						-3	CHANNEL 3	
	CHANNEL 3						-2	CHANNEL 2	
	CHANNEL 4						-1	CHANNEL 1	
SPACE				SPACE					
SPACE				SPACE					
INSTALLING CONTRACTOR TO USE: 16 AWG, BELDEN 6200 UE OR EQUAL; REFERENCE 2-WIRE DATA BUS WIRING DETAIL									