

PANEL NAME:				IP ADDRESS:		N/A	
MOUNTING LOCATION:				SUBNET MASK:		N/A	
TRANSFORMER FEED:				DEFAULT GATEWAY:		N/A	
PANEL TYPE:		NXL-D16i		PANEL DIMENSIONS:		24.00"H x 20.00"W x 6.00"D	
LEFT SIDE				RIGHT SIDE			
LOAD DESCRIPTION	SOURCE	ADDRESS	DEVICE	DEVICE	ADDRESS	SOURCE	LOAD DESCRIPTION
CRC2180 RELAY CONTROLLER				CRC7000	-1		
				CRC7000	-2		
CRC2180 RELAY CONTROLLER				CRC7000	-3		
				CRC7000	-4		
	CHANNEL 1		-1	CRC4214 0-10 DIMMER	CRC7000	-1	
	CHANNEL 2		-2		CRC7000	-2	
	CHANNEL 3		-3		CRC7000	-3	
	CHANNEL 4		-4		CRC7000	-4	
	CHANNEL 1		-1	CRC4214 0-10 DIMMER	CRC7000	-3	
	CHANNEL 2		-2		CRC7000	-4	
	CHANNEL 3		-3		CRC7000	-1	
	CHANNEL 4		-4		CRC7000	-2	
	CHANNEL 1		-1	CRC4214 0-10 DIMMER	CRC7000	-1	
	CHANNEL 2		-2		CRC7000	-2	
	CHANNEL 3		-3		CRC7000	-3	
	CHANNEL 4		-4		CRC7000	-4	
	CHANNEL 1		-1	CRC4214 0-10 DIMMER	CRC7000	-3	
	CHANNEL 2		-2		CRC7000	-4	
	CHANNEL 3		-3		CRC7000	-1	
	CHANNEL 4		-4		CRC7000	-2	
CRC6001 (AMP) SPACE FOR AMPLIFIER				CRC7000	-1		
				CRC7000	-2		
				CRC7000	-3		
				CRC7000	-4		
				SPACE			



INSTALLING CONTRACTOR TO USE: 16 AWG, BELDEN 6200 UE OR EQUAL; REFERENCE 2-WIRE DATA BUS WIRING DETAIL